

RICOH
imagine. change.

M C250FW/P C301W

M C250FW

P C301W

GENERAL

Configuration	Desktop	
Technology	Laser	
Warm-up time	20 seconds	
First copy speed: B/W	9.4 seconds	
First copy speed: full colour	9.8 seconds	
Continuous output speed	25 ppm	
Memory: standard	256 MB	
Memory: maximum	256 MB	
SPDF capacity	sheets	-
Duty cycle	65,000	
Duplex	Yes	
Weight	30 kg	25 kg
Dimensions: W x D x H	420 x 493 x 473 mm	400 x 450 x 334 mm
Power source	220 - 240 V, 50 - 60 Hz	



COPIER (M C250FW)

Multiple copying	Up to 99 copies	-
Zoom	From 25% to 400% in 1% steps	-
ID card copy	Yes	-

PRINTER

Printing process	Laser beam scanning, electro-photographic printing	
Printer language: standard	PCL5c PCL6 PostScript® 3™	
Print resolution	Maximum: : 2,400 x 600 dpi	
Font	Standard: : PCL (80 fonts), PS3 (80 fonts)	
Network interface: standard	Ethernet 10 base-T/100 base-TX Wireless LAN (IEEE 802.11 a/b/g/n) USB 2.0	
Mobile printing capability	Apple AirPrint Mopria® Google Cloud Print	
Windows® environments	Windows® 7 Windows® 8.1 Windows® 10 Windows® Server 2008 Windows® Server 2008R2 Windows® Server 2012 Windows® Server 2012R2 Windows® Server 2016	
Mac OS environments	Macintosh OS X v10.10 - v10.13	
Other supported environments	Linux environment	

SCANNER (M C250FW)

Scanning: B/W	21 ipm	-
Scanning: full colour	12 ipm	-
Resolution: maximum	19,200 dpi	-
Resolution: standard	600 dpi	-
Bundled drivers	Network TWAIN	-
Scan modes	E-mail, Folder, USB	-

FAX (M C250FW)

Circuit	PSTN	-
Compatibility	ITU-T(T.37) Internet-Fax, T30 (ITU-T Super G3)	-
Transmission speed	seconds	-
Modem speed: maximum	Kbps	-
Internet fax	Standard	-
LAN fax	Standard	-

PAPER HANDLING

Recommended paper size	A4 A5 A6 B4 B5
Paper input: standard	250 sheets
Paper input: bypass (standard)	1 sheets
Paper input: maximum	751 sheets
Paper output: standard	150 sheets

Paper weight	Trays : 60 - 163 g/m ² Optional tray(s) : 60 - 105 g/m ² Bypass : 60 - 163 g/m ² Duplex : 60 - 90 g/m ²
--------------	--

ECOLOGY

Power consumption: max.	< 1,300 W	
TEC*	0.31 kWh/week	0.3 kWh/week

INPUT/OUTPUT TRAYS AND FINISHER OPTIONS

1x 500-sheet paper tray

COMMISSION REGULATION (EU) 2019/2020. The light source of this product is not intended for applications other than image printing.

ISO9001 certified, ISO14001 certified, ISO27001 certified

All brand and/or product names are trademarks of their respective owners.

Specifications and external appearance are subject to change without notice. The images in this brochure are not real photographs and slight differences in detail might appear, including in relation to colour. Not all services and solutions are available to all customers.

Copyright © 2024 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.

RICOH
imagine. change.